




IP65 Strong

674×90×68mm




AC176-264V
Package size of the lamp:
706×98×56mm
PF ≥ 0,97



○ metal

Article	Power	Light temperature	Luminous flux*	Matt Diffuser	Clear Diffuser
V1-I0-70215-03000-6501840	18W	4000K	2100lm		
V1-I0-70215-03000-6501850	18W	5000K	2100lm		
V1-I0-70215-03000-6501865	18W	6500K	2200lm		
V1-I0-70215-03000-6502740	27W	4000K	3150lm		
V1-I0-70215-03000-6502750	27W	5000K	3150lm		
V1-I0-70215-03000-6502765	27W	6500K	3300lm		



DC24-36V
PF ≥ 0,97



○ metal

Article	Power	Light temperature	Luminous flux*	Matt Diffuser	Clear Diffuser
V1-I0-70215-03N00-6501840	18W	4000K	2100lm		
V1-I0-70215-03N00-6501850	18W	5000K	2100lm		
V1-I0-70215-03N00-6501865	18W	6500K	2200lm		

Installation:

Mount directly on a horizontal or vertical surface
Can be mounted on hangers

Case:

High impact self-extinguishing ABS plastic
It is completed with wearproof cable input

Diffuser:


Polycarbonate with UV stabilizer additives
Mounted to the body of the lamp on the latches

Specifications:

Index of color transmission Ra > 80
Temperature range from -40 °C to + 45 °C
Network frequency 50Hz ± 10%
LED life 50,000 hours
3 year warranty
Luminous flux Kn <1%



IP65 Strong
674×90×68mm




DALI

AC176-264V
PF ≥ 0,97

NEW MODEL

Article	Power	Light temperature	Luminous flux*	Matt Diffuser	Clear Diffuser
V1-I0-70215-03D01-6501840	18W	4000K	2100lm		
V1-I0-70215-03D01-6501850	18W	5000K	2100lm		
V1-I0-70215-03D01-6501865	18W	6500K	2200lm		

IP65 Strong
674×90×68mm





Autonomous emergency lamp constant action

NEW MODEL

Emergency power supply unit battery for 1 hour of autonomous operation, charge indicator, "Test" button in the set (see description on page 266)

Conformity:
Standard IEC 60598-2-22-2012 «Luminaires. Part 2-22. Private requirements. Luminaires for emergency lighting »
SP 52. 13330. 2011 "Natural and artificial lighting" (updated edition of SNiP 23.05-95)

Article	Power	Light temperature	Luminous flux*
V1-I0-70215-03A00-6501840	18W	4000K	2100lm
V1-I0-70215-03A00-6501850	18W	5000K	2100lm
V1-I0-70215-03A00-6501865	18W	6500K	2200lm




AC176-264V
PF ≥ 0,97

NEW MODEL

metal

Article	Power	Light temperature	Luminous flux*	Matt Diffuser	Clear Diffuser
V1-I0-70215-03S00-6501840	18W	4000K	2100lm		
V1-I0-70215-03S00-6501850	18W	5000K	2100lm		
V1-I0-70215-03S00-6501865	18W	6500K	2200lm		



* Luminous flux is specified without Diffuser

