




Strong 2.0

674×90×68mm





AC176-264V
Package size of the lamp:
674×90×68mm

$K_{T1} < 2\%$
 $PF \geq 0,95$
 $R_a > 84$




Article	Power	Light temperature	Luminous flux*	Diffuser
V1-12-70215-03G02-6501665	16W	6500K	1920lm	Matt
V1-12-70215-03G00-6501665	16W	6500K	2080lm	Clear
V1-12-70215-03G02-6501650	16W	5000K	1920lm	Matt
V1-12-70215-03G00-6501650	16W	5000K	2080lm	Clear
V1-12-70215-03G02-6501640	16W	4000K	1920lm	Matt
V1-12-70215-03G00-6501640	16W	4000K	2080lm	Clear
V1-12-70215-03G02-6501630	16W	3000K	1728lm	Matt
V1-12-70215-03G00-6501630	16W	3000K	1872lm	Clear



DC24-36V
PF $\geq 0,97$



Article	Power	Light temperature	Luminous flux*	Diffuser
V1-12-70215-03N02-6501665	16W	6500K	1920lm	Matt
V1-12-70215-03N00-6501665	16W	6500K	2080lm	Clear
V1-12-70215-03N02-6501650	16W	5000K	1920lm	Matt
V1-12-70215-03N00-6501650	16W	5000K	2080lm	Clear
V1-12-70215-03N02-6501640	16W	4000K	1920lm	Matt
V1-12-70215-03N00-6501640	16W	4000K	2080lm	Clear
V1-12-70215-03N02-6501630	16W	3000K	1728lm	Matt
V1-12-70215-03N00-6501630	16W	3000K	1872lm	Clear



Installation:

Mount directly on a horizontal or vertical surface
Can be mounted on hangers

Case:

High impact self-extinguishing ABS plastic
It is completed with wearproof cable input

Diffuser:

Polycarbonate with UV stabilizer additives
Mounted to the body of the lamp on the latches


Specifications:

Index of color transmission $R_a > 80$
Temperature range from -40°C to $+45^\circ\text{C}$
LED life 50,000 hours
3 year warranty
Luminous flux $K_n < 2\%$



Strong 2.0

674×90×68mm




DALI

AC176-264V
PF ≥ 0,97

Article	Power	Light temperature	Luminous flux*	Diffuser	Clear Diffuser
V1-I2-70215-03D02-6501665	16W	6500K	1920lm	Matt	
V1-I2-70215-03D00-6501665	16W	6500K	2080lm	Clear	
V1-I2-70215-03D02-6501650	16W	5000K	1920lm	Matt	
V1-I2-70215-03D00-6501650	16W	5000K	2080lm	Clear	
V1-I2-70215-03D02-6501640	16W	4000K	1920lm	Matt	
V1-I2-70215-03D00-6501640	16W	4000K	2080lm	Clear	
V1-I2-70215-03D02-6501630	16W	3000K	1728lm	Matt	
V1-I2-70215-03D00-6501630	16W	3000K	1872lm	Clear	

Strong 2.0

674×90×68mm





Autonomous emergency lamp constant action

Emergency power supply unit battery for 1 hour of autonomous operation, charge indicator, "Test" button in the set (see description on page 266)

Conformity:


Standard IEC 60598-2-22-2012 «Luminaires. Part 2-22. Private requirements. Luminaires for emergency lighting »
SP 52. 13330. 2011 "Natural and artificial lighting" (updated edition of SNiP 23.05-95)

Article	Power	Light temperature	Luminous flux*	Diffuser	Clear Diffuser
V1-I2-70215-03A02-6501665	16W	6500K	1920lm	Matt	
V1-I2-70215-03A00-6501665	16W	6500K	2080lm	Clear	
V1-I2-70215-03A02-6501650	16W	5000K	1920lm	Matt	
V1-I2-70215-03A00-6501650	16W	5000K	2080lm	Clear	
V1-I2-70215-03A02-6501640	16W	4000K	1920lm	Matt	
V1-I2-70215-03A00-6501640	16W	4000K	2080lm	Clear	
V1-I2-70215-03A02-6501630	16W	3000K	1728lm	Matt	
V1-I2-70215-03A00-6501630	16W	3000K	1872lm	Clear	



AC176-264V
PF ≥ 0,97

metal



Article	Power	Light temperature	Luminous flux*	Diffuser	Clear Diffuser
V1-I2-70215-03S02-6501665	16W	6500K	1920lm	Matt	
V1-I2-70215-03S00-6501665	16W	6500K	2080lm	Clear	
V1-I2-70215-03S02-6501650	16W	5000K	1920lm	Matt	
V1-I2-70215-03S00-6501650	16W	5000K	2080lm	Clear	
V1-I2-70215-03S02-6501640	16W	4000K	1920lm	Matt	
V1-I2-70215-03S00-6501640	16W	4000K	2080lm	Clear	
V1-I2-70215-03S02-6501630	16W	3000K	1728lm	Matt	
V1-I2-70215-03S00-6501630	16W	3000K	1872lm	Clear	

* Luminous Flux Set excluding the diffuser

