
ROTATIS 173 FullHD Retractable, Rotating Monitor





Retractable, Rotating Monitor





"What is ROTATIS?"

Within ROTATIS rests a retractable monitor whose display can be either in the upright position constantly or closed over for later retraction, in a circular turntable.

This is incorporated into the furniture surface via a separate frame, allowing for the entire construction to be

parate frame, allowing for the entire construction to be contained in a single piece, requiring no further adjustment externally. Allows the rotation of the rotation of the monitor to 350°. Its ideal for use where multiple users at a time should see content on the screen or where a single user inputs data then rotates the screen for verification & authentication

A design first & fully customisable. Often Copied - Never Equalled.

MADE IN GERMANY.

More than 15 years know-how in monitor-design. Warranty 5 years mechanics, 2 years electric and electronic, 10 years spare part availability.

Sleek. Silent. Svelte. Handcrafted & tested to ensure the highest standards.

Reliable partner with solid repeat business across diverse client fields. Global references and project experiences.



- Custom Plexiglass Trim Colour
- Custom Logo



Retractable, Rotating Monitor



GENERAL SPECIFICATIONS

Functionality mechanical rotary plate with motorized

retractable monitor; 2x integrated USB

sockets

Motor and mechanics 12 V stepper motor with simultaneous drive for multiple monitors (up to 80%)

more quiet as a brush motormaintenance

Material Monitor surface in toughened 3 mm anti-

reflective coated glass pane, main housing brushed anodized aluminium, high quality brushed steel framework and display

enclosure

Dimensions Rotary plate Ø 700 mm, 113 (depth)

Weight 30 kg total weight

Inclination 8°

Installation altitude 299 mm

Monitor FULL HD, 17.3" TFT

HDCP compatible Active Matrix, widescreen format, LED Backlight

Brightness 400 cd/m² 600:1

Contrast ratio 600:1

Resolution (dots) 920 (h) x 1080 (v), Full HD (16:9)

Pixelsize 0.1989 (h) x 0.1989 (v) mm

Viewing angle 60°/80° u/d, 80°/80° l/r

Viewing area 381.888 (h) x 214.812 (v) mm

LED life time up to 50,000 hrs

Video interface HDMI, VGA optional

Remote Control TCP/IP on-board via RJ45

9-PIN d-sub serial

For device control, setup of the movement parameter, firmware-Update

(E1-cable and software required)

Power Consumption 15W

Certifications TüV, CE, FCC

Warranty 5 Years Mechanical / 2 Years Optical

Extendable at inception with surcharge

E&OE.

Sustainable materials and manufacturing

SCOPE OF SUPPLY

External power supply, power cord, output: 12V, 5A, input: 100-240 V,

50/60 Hz, 1,5 A wired remote control

AVAILABLE OPTIONS

Custom colour (anodizing or coated)
Custom colour plexiglass trim
Custom Logo additional
Multi-Touch Overlay
Full HD camera/ max. 5 MP
HDMI instead of USB socket



Retractable, Rotating Monitor





Applications

Banks

Consulting

POS

Lounge

Concierge






Retractable, Rotating Monitor





Table cutting

side viewing




view from above





Nothing to talk about. Cut out, put in, plug in.



Retractable, Rotating Monitor



ROTATIS

