



## ANTARES-4 TRIMLESS

### ROUND ADJUSTABLE TRIMLESS REDUCED GLARE DOWNLIGHT

- Compatible with the 35 and 50 series ELR LED modules
- Colour temperature options: 2700K, 3000K, 4000K, 5000K, tuneWHITE™
- Colour rendering index: 85 or 95
- Up to 50,000 hour L70 lamp life with LM80 tested LED chip packages
- Beam pattern options: 12°, 20°, 35°, 60°
- Luminous flux: 800lm to 1650lm (depending on LED module)
- Supplied with non, phase, 0-10V or DALI dimmable LED driver
- Trimless with plastered ceiling
- 103mm cutout
- +30° gimbal tilt
- 0-355° rotatable horizontal axis
- ATePS™ Automated Thermal Protection System
- Interchangeable LED module system
- For the latest specifications please refer to the website

the information above is at nominal values accuracy of +/-7%  
\*ATePS™ Automated Thermal Protection System is the trademark of ELR

#### AVAILABLE OPTIONS

**BEAM ANGLE**

**TEMPERATURE**  
2700K, 3000K, 4000K, 5000K

**tuneWHITE™ (DALI TYPE 8, PART 209)**  
TUNABLE COLOUR TEMPERATURE FROM 2700K TO 5000K

**DRIVER**

(ND)	(PH)	(AN)	(DA)




reddot design award  
winner 2012

#### TRIM COLOUR OPTIONS



#### DIMENSIONS (MM)



\*tuneWHITE models are available for 50P, 100P and 300P modules and is compatible with DALI driver only  
§12° beam angle options is for specification project only, please consult manufacturer for availability lead time



Data will be subject to change without notice.