



ANTARES 4

ROUND ADJUSTABLE REDUCED GLARE DOWNLIGHT

- Compatible with the 35 and 50 series ELR LED modules
- Colour temperature options: 2700K, 3000K, 4000K, 5000K, tuneWHITE™
- Colour rendering index: 85 or 95
- Up to 50,000 hour L70 lamp life with LM80 tested LED chip packages
- Beam pattern options: 12°, 20°, 35°, 60°
- Luminous flux: 800lm to 1650lm (depending on LED module)
- Supplied with non, phase, 0-10V or DALI dimmable LED driver
- 3mm trim width
- 100mm cutout
- +/-30° gimbal tilt (for 35 series module)
- +/-20° gimbal tilt (for 50 series module)
- 0-355° rotatable horizontal axis
- ATePS™ Automated Thermal Protection System
- Interchangeable LED module system
- For the latest specifications please refer to the website

the information above is at nominal values accuracy of +/-7%

*ATePS™ Automated Thermal Protection System is the trademark of ELR

AVAILABLE OPTIONS

BEAM ANGLE

TEMPERATURE
2700K, 3000K, 4000K, 5000K

tuneWHITE™ (DALI TYPE 8, PART 209)
TUNABLE COLOUR TEMPERATURE FROM 2700K TO 5000K

DRIVER

(ND)	(PH)	(AN)	(DA)




reddot design award
winner 2012

TRIM COLOUR OPTIONS



DIMENSIONS (MM)



*tuneWHITE models are available for 50P, 100P and 300P modules and is compatible with DALI driver only
§12° beam angle options is for specification project only, please consult manufacturer for availability lead time



Data will be subject to change without notice.