

Intimidator® AGM Solutions for Intimidating Battery Needs

Intimidator is a pioneer brand in the development of the form, fit, and function of AGM battery technology. It has been tested and proven to best meet the criteria for the various types of dependable marine power needs.



ADVANCED DURABILITY DESIGNS

- Fortified posts, straps, and welds resist vibration damage
- Maximize current transfer over life of battery



POWER-PERFORM FULL-FRAME POSITIVE & NEGATIVE PLATES

- Better withstands rigorous marine demands
- Prevents life-robbing electrical shorts from exposed wire



ENHANCED ELECTROLYTE SUSPENSION SYSTEM

- Absorbs more electrolyte, protects internal components
- Micro-porous glass separators prevents acid spills and terminal corrosion

MARINE/RV	INTIMIDATOR®	AGM BATTERIES

GROUP PART		PERFORMANCE LEVEL			APPROX.	MAXIMUM OVERALL DIMENSIONS							
NO. NO.	CCA RES.	RES.	REF. 20 AH	WEIGHT	Length		Width		Height		FOOTNOTES		
		@ 0°F	CAP.	MCA RATE	(lbs.)	inch	mm	inch	mm	inch	mm		
		DUAL PL	JRPOSE A	BSORBE	D GLASS	MAT (AC	AV (ME	LVE	REGULA	ATED			
34M	9A34M	775	120	955	55	42.5	10¾	273	6%	175	8%	212	2,17,46,78,U
12 VOLT HEAVY-DUTY DEEP CYCLE ABSORBED GLASS MAT (AGM) VALVE REGULATED													
U1	8AU1	200	45	240	32	23	7 3/4	197	5 1/8	130	7 1/4	184	2,38,39,44,Y
U1	8AUIH	200	45	240	32	23	8 1/16	211	5 1/8	130	7 1/4	184	2,17,38,39,44,Y
22NF	8A22NF	350	85	420	55	37	9	228	5 ½	140	9 1/4	235	2,38,39,44,G
24M	8A24M	525	135	800	79	52	10 %	276	6 ¾	171	9 %	238	2,17,38,39,44,U
27M	8A27M	580	175	900	92	61.5	12 ¾	324	6 ¾	171	9 %	238	2,17,38,39,44,U
31M	8A31DTM	800	200	1000	105	67.5	12 ¹⁵ / ₁₆	329	6 ¾	171	9 %	238	2,16,17,38,39,44,A
4D	8A4D	1110	380	1420	198	131.5	20 ¾	527	8 ½	216	10	254	2,17,44\$
8D	8A8D	1450	480	1800	245	163	20 ¾	527	11	279	10	254	2,17,44S
	6 VOLT H	IEAVY-DU	TY DEEP	CYCLE A	BSORBE	D GLASS	MAT ((AGM)	VALVI	E REG	ULAT	ED	
GC2	8AGC2	680	380	900	190	68	10 1/4	260	7 1/8	181	10 %	276	2,44,U

All batteries have SAE automotive posts unless noted

FOOTNOTES: 2. Black cover / Gray case 16. Dual terminal universal design 17. Includes handle 38. "Non-spillable" defined by DOT (Department of Transportation) definitions 39. "Non-spillable" defined by ICAO (International Commercial Airline Organization) and IATA (International Airline Transport Association) definitions 44. Free replacement warranty is 3 months in full electric vehicle use. 46. If battery is used in on-highway vehicles equipped with 2-way radios (such as taxis, police, and emergency vehicles), marine applications, off-highway use, and other non-automotive usage, Free warranty replacement period will be 18 months. Free replacement warranty is 12 months in deep-cycle use, and 3 months in full electric vehicle use. 78. Shipped withy 22mm height adapter. A. Flush combination terminal w/ 3/8" stud and SAE post, hex nut included. G. Offset post w/ horizontal hole, stainless steel 5/16" bolt and hex nut (T881) U. Molded-in offset SAE post and vertical 5/16" NEG., 5/16" POS. stainless steel studs & hex nuts Y. Small L terminal with round holes. S. SAE "Automotive type" post (TSAE).

PROPOSITION 65 WARNING: Battery posts, terminals and related accessories contain lead and lead compounds, chemicals known to the State of California to cause cancer and reproductive harm. Batteries also contain other chemicals known to the State of California to cause cancer. WASH HANDS AFTER HANDLING.

Experience the East Penn Advantage

East Penn's A³ TM Advanced-Cubed precision-focused manufacturing approach ensures the process behind the technology delivers critical quality at each stage of battery production. INTIMIDATOR batteries are supported by A³ manufacturing to optimize the life, power, and durability of the battery's design and performance.



Fax: 610-682-4781











East Penn Manufacturing Co. Lyon Station, PA 19536-0147 Phone: 610-682-6361

www.eastpenn-deka.com