
# CONVERS 220 FullHD / Tilt Vertically Retractable Monitor





['vɪʒu'lu:ʒəneri] ADJ:

describes the feeling and impression you get when you use unique integrated monitor solutions from ELEMENT ONE ™





Vertically Retractable Monitor



#### "What is CONVERS?"

CONVERS is a true marvel of functionality, engineering & design. All that is visible in the retracted state is the slender brushed steel cover. With a single touch the display panel elevates with a whisper from the housing below. Designed to encourage interaction within the meeting space it can then disappear as silently & quickly as it appeared to allow the parties' interaction & discourse to continue un-obstructed.

additional feature at model CONVERS 220 Tilt: automatically tilting to the preset user angle A design first & fully customisable. Often Copied - Never Equalled.

MADE IN GERMANY.

More than 15 years know-how in monitor-design. Warranty 5 years mechanics, 2 years electric and electronic, 10 years spare part availability.

Sleek. Silent. Svelte. Handcrafted & tested to ensure the highest standards. Reliable partner with solid repeat business across diverse client fields. Global references and project experiences.





## CONVERS 220 FullHD / Tilt Vertically Retractable Monitor




| GENERAL SPEC                                                                        | CIFICATIONS                                                                                                                                                                                                                                    | CONVERS 220 Tilt:<br>separate motorization | Video Interface                                                                                                                                                                                                                                                      | HDMI                                                                                                                                                          |
|-------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Functionality                                                                       | Motorised Screen<br>Single Touch electronic Anti Clamp<br>Protection                                                                                                                                                                           |                                            |                                                                                                                                                                                                                                                                      | VGA Optional<br>Firmware Update – external via signal<br>cable                                                                                                |
| Motor & Mechanics<br>CONVERS 220 Tilt:<br>Second motorization<br>for tilt mechanism | 12V Step Motor with simultaneous drive<br>for multiple movements.<br>Maintenance Free<br>Virtually Silent – 40 dB                                                                                                                              |                                            | Remote Control                                                                                                                                                                                                                                                       | TCP/IP on-board via RJ45<br>9-PIN d-sub serial<br>For device control, setup of the<br>movement parameter, firmware-Update<br>(E1-cable and software required) |
| Material                                                                            |                                                                                                                                                                                                                                                |                                            | Power Consumption                                                                                                                                                                                                                                                    | 15W                                                                                                                                                           |
|                                                                                     | Chassis & Carto<br>grade steel                                                                                                                                                                                                                 | uche - Brushed high-                       | Certifications                                                                                                                                                                                                                                                       | TüV, CE, FCC                                                                                                                                                  |
| Display                                                                             | 3 mm Antireflective coated protective glass                                                                                                                                                                                                    |                                            | Warranty                                                                                                                                                                                                                                                             | 5 Years Mechanical / 2 Years Optical<br>Extendable at inception with surcharge<br>E&OE<br>Sustainable materials and manufacturing                             |
| Dimensions                                                                          | 620 x 100 x 587 mm                                                                                                                                                                                                                             |                                            |                                                                                                                                                                                                                                                                      | Sustainable materials and manufacturing                                                                                                                       |
| Weight                                                                              | 17.4 kg<br>CONVERS 220 Tilt:                                                                                                                                                                                                                   |                                            | SCOPE OF SUPPLY                                                                                                                                                                                                                                                      |                                                                                                                                                               |
| Inclination                                                                         | 15°                                                                                                                                                                                                                                            | inclination 15°,<br>elevated height        |                                                                                                                                                                                                                                                                      |                                                                                                                                                               |
| Elevated Height                                                                     | 365 mm                                                                                                                                                                                                                                         | 322 mm at 105°                             | External Power Supply<br>Power Cord – 1.5 m                                                                                                                                                                                                                          |                                                                                                                                                               |
| Monitor                                                                             | Full HD 21.5" LED Backlit TFT<br>HDCP Compatible<br>Active Matrix<br>Widescreen Format<br>250 cd/m <sup>2</sup><br>1000:1<br>1920 x 1080 – Full HD (16:9)<br>0.1989 x 0.1989 mm<br>Horizontal 178°/ Vertical - 178°<br>475,20 (H) x 267,30 (V) |                                            | Output: 12V, 5A<br>Input: 100 - 240V, 50/60Hz, 1,5A<br>AVAILABLE OPTIONS                                                                                                                                                                                             |                                                                                                                                                               |
| Brightness                                                                          |                                                                                                                                                                                                                                                |                                            | Integration from Below – R Version<br>Custom Colour – Anodization or Coating<br>Custom Plexiglass Trim Colour<br>Custom Logo<br>Multi Touch Overlay<br>Additional sockets – USB / XLR / Phono / Video<br>Leather Trim<br>Double Full HD cam<br>Conference Microphone |                                                                                                                                                               |
| Contrast Ratio                                                                      |                                                                                                                                                                                                                                                |                                            |                                                                                                                                                                                                                                                                      |                                                                                                                                                               |
| Resolution                                                                          |                                                                                                                                                                                                                                                |                                            |                                                                                                                                                                                                                                                                      |                                                                                                                                                               |
| Pixel size                                                                          |                                                                                                                                                                                                                                                |                                            |                                                                                                                                                                                                                                                                      |                                                                                                                                                               |
| Viewing Angle                                                                       |                                                                                                                                                                                                                                                |                                            |                                                                                                                                                                                                                                                                      |                                                                                                                                                               |
| Viewing Area                                                                        |                                                                                                                                                                                                                                                |                                            |                                                                                                                                                                                                                                                                      |                                                                                                                                                               |
| LED Lifespan                                                                        | Up to 50,000 hrs                                                                                                                                                                                                                               | S                                          |                                                                                                                                                                                                                                                                      |                                                                                                                                                               |





Vertically Retractable Monitor






Vertically Retractable Monitor


Nothing to talk about.

Cutout, put in, plug in.




ELEMENT

**ONE** 



Vertically Retractable Monitor







ELEMENT ONE Multimedia GmbH Zum Murgdamm 5 D-76456 Kuppenheim Germany fon +49 (0) 7222 96654-0 fax +49 (0) 7222 96654-29 www.elementonescreens.com info@elementonescreens.com